



## A blue Vention tablet with a colorful ring on top. The brand name 'VENTION' is visible on the top bezel.




Figure 4. Macrolactolysis with Pendant  $\beta$ -D.

- Plug and Play compatibility with Macintosh/Windows 3.11 controller
- Pre-installed Macintosh/Win. for easy, fast automation sequence setting
- Application software for machine operation
- Manual machine operation mode
- Robot and accessories in desired I/O/T network
- Front and rear locking system for Remote Support function (for less purchased dependency)
- Safety RS & Safety GUT connectors for doing working on "Workless safety" step
- Volume & Power Indicator
- Removable handle

**Privacy Policy**

1. Purpose of the Policy: The purpose of this policy is to inform you of the ways in which we collect, use, and disclose your personal information, and to provide you with the opportunity to opt-out of the collection, use, and disclosure of your personal information.

2. Scope of the Policy: This policy applies to all personal information collected, used, and disclosed by the Company, its subsidiaries, and its affiliates, and to all personal information collected, used, and disclosed by the Company, its subsidiaries, and its affiliates, and to all personal information collected, used, and disclosed by the Company, its subsidiaries, and its affiliates.

3. Collection of Personal Information: The Company collects personal information from you when you use the Company's services, products, or applications, or when you provide information to the Company, its subsidiaries, or its affiliates. The Company collects personal information from you when you use the Company's services, products, or applications, or when you provide information to the Company, its subsidiaries, or its affiliates.

4. Use of Personal Information: The Company uses personal information for the purposes of providing you with the Company's services, products, or applications, and for the purposes of improving the Company's services, products, or applications. The Company uses personal information for the purposes of providing you with the Company's services, products, or applications, and for the purposes of improving the Company's services, products, or applications.

5. Disclosure of Personal Information: The Company may disclose personal information to its subsidiaries, affiliates, or service providers, or to other third parties, for the purposes of providing you with the Company's services, products, or applications, and for the purposes of improving the Company's services, products, or applications. The Company may disclose personal information to its subsidiaries, affiliates, or service providers, or to other third parties, for the purposes of providing you with the Company's services, products, or applications, and for the purposes of improving the Company's services, products, or applications.

6. Security of Personal Information: The Company takes reasonable steps to protect personal information from unauthorized access, use, or disclosure. The Company takes reasonable steps to protect personal information from unauthorized access, use, or disclosure.

7. Your Rights: You have the right to access, update, or delete your personal information, and you have the right to opt-out of the collection, use, and disclosure of your personal information. You have the right to access, update, or delete your personal information, and you have the right to opt-out of the collection, use, and disclosure of your personal information.

8. Contact Us: If you have any questions or concerns about this policy, please contact us at [contact information]. If you have any questions or concerns about this policy, please contact us at [contact information].

● The Pendant V3 can only be connected to function safety devices.

● The Pendant V3 is designed to operate in indoor environments without dust or high humidity. Dust and dampness may lead to malfunction. Do not install or operate the Safety Shuttle outside.



**Figure 3 Control Center**

[illegible]

Figure 3. Mortality only.

The screenshot shows the VERTICA web interface. On the left is a sidebar with navigation links: Home, Overview, Recent Queries, Recent Databases, Recent Tables, Recent Views, Recent Schemas, Recent Users, Recent Roles, Recent Groups, Recent Clusters, Recent Nodes, Recent Jobs, Recent Alerts, Recent Logs, Recent Metrics, Recent Configs, Recent Settings, Recent Status, Recent Health, Recent Performance, Recent Security, Recent Compliance, Recent Audit, Recent Backup, Recent Restore, Recent Upgrade, Recent Patch, Recent Update, Recent Install, Recent Uninstall, Recent Reinstall, Recent Repair, Recent Replace, Recent Refresh, Recent Recreate, Recent Drop, Recent Truncate, Recent Vacuum, Recent Analyze, Recent Explain, Recent Profile, Recent Monitor, Recent Debug, Recent Test, Recent Demo, Recent Sandbox, Recent Playground, Recent Training, Recent Research, Recent Experiment, Recent Prototype, Recent PoC, Recent Pilot, Recent Production, Recent Deployment, Recent Release, Recent Version, Recent Build, Recent Package, Recent Artifact, Recent Container, Recent Image, Recent Registry, Recent Repository, Recent Marketplace, Recent Catalog, Recent Index, Recent Search, Recent Filter, Recent Sort, Recent Group, Recent Sort, Recent Filter, Recent Group, Recent Sort, Recent Filter, Recent Group.

The main content area displays the results of the query `SELECT * FROM test;`. The results are shown in a table with 10 columns: `id`, `name`, `age`, `gender`, `height`, `weight`, `hair_color`, `eye_color`, `skin_color`, and `last_name`. The table contains 10 rows of data. At the bottom right of the interface, there are two buttons: a green button with a right-pointing arrow and a grey button with a square icon.

[illegible]

### Class B Manual Mode

[illegible]

Entity ID	Entity ID	Entity ID	Description
1	101	101	101
2	102	102	102
3	103	103	103
4	104	104	104
5	105	105	105
6	106	106	106
7	107	107	107
8	108	108	108
9	109	109	109
10	110	110	110
11	111	111	111
12	112	112	112
13	113	113	113
14	114	114	114
15	115	115	115
16	116	116	116
17	117	117	117
18	118	118	118
19	119	119	119
20	120	120	120
21	121	121	121
22	122	122	122
23	123	123	123
24	124	124	124
25	125	125	125
26	126	126	126
27	127	127	127
28	128	128	128
29	129	129	129
30	130	130	130
31	131	131	131
32	132	132	132
33	133	133	133
34	134	134	134
35	135	135	135
36	136	136	136
37	137	137	137
38	138	138	138
39	139	139	139
40	140	140	140
41	141	141	141
42	142	142	142
43	143	143	143
44	144	144	144
45	145	145	145
46	146	146	146
47	147	147	147
48	148	148	148
49	149	149	149
50	150	150	150
51	151	151	151
52	152	152	152
53	153	153	153
54	154	154	154
55	155	155	155
56	156	156	156
57	157	157	157
58	158	158	158
59	159	159	159
60	160	160	160
61	161	161	161
62	162	162	162
63	163	163	163
64	164	164	164
65	165	165	165
66	166	166	166
67	167	167	167
68	168	168	168
69	169	169	169
70	170	170	170
71	171	171	171
72	172	172	172
73	173	173	173
74	174	174	174
75	175	175	175
76	176	176	176
77	177	177	177
78	178	178	178
79	179	179	179
80	180	180	180
81	181	181	181
82	182	182	182
83	183	183	183
84	184	184	184
85	185	185	185
86	186	186	186
87	187	187	187
88	188	188	188
89	189	189	189
90	190	190	190
91	191	191	191
92	192	192	192
93	193	193	193
94	194	194	194
95	195	195	195
96	196	196	196
97	197		

		Example
1	201	
2	201	
3	MonthName(SalesChannel) = 'Online' 1	
4	MonthName(SalesChannel) = 'Online' 2	
5	MonthName(SalesChannel) = 'Online' 1	
6	MonthName(SalesChannel) = 'Online' 2	
7	None (Online)	
8	None (Online)	
9	None (Online)	
10	None (Online)	
11	None (Online)	
12	None (Online)	
13	None (Online)	
14	None (Online)	
15	None (Online)	

Item	Specification
Enrich vocabulary	Endowment validated as per (EC-4588.2.3)
Ingress protection	(IP)
Mounting	<ul style="list-style-type: none"> <li>■ VESA-mounting holes</li> <li>■ Mounting bracket compatible (<a href="#">37, 48, 60, 80mm</a>)</li> </ul>

**Power Button Functionality**

- Pressing once on the power button while the Pendant is in OFF will power it ON.
- Pressing more than 12 seconds on the power button while the Pendant is ON will power it OFF.
- The Pendant goes into low brightness mode after 30 seconds of continuous pressing once on the power button while the Pendant is ON and its low brightness mode changes the display to full brightness.
- If the Pendant is not connected to a television, it will remain in low brightness mode after 30 seconds.
- The Pendant V3 includes 2 optional remote primary controls (as shown in Figures 4.6.7) which can be installed by the user if required.

The pendant's VFD displays an emergency stop location which is connected to the safety loop of a laser installation.

When evaluating the performance of a safety function utilizing the pendant (3) attention shall be made in regards to the number of delay chained emergency stop buttons and interlock devices. Fault masking reduces the performance level of the safety function. Guidance on fault masking can be found in IEC 61508-2:45.

	Date	Value	Unit
$\rho_{\text{air}}$	20		kg/m <sup>3</sup>
$\rho_{\text{w}}$	10		kg/m <sup>3</sup>
$\eta_{\text{w}}$	2000		kg/m <sup>3</sup>

**EU Declaration of Conformity**

[Documentation for Previous Product Versions](#)